



INFINITY MIB-2P-C

Key Feature

- 2MP Resolution
- 24/7 Full Color
- 2.8mm fixed lens
- H.265 compression
- Light Range up to 25M
- Support ONVIF 2.4
- Support PoE
- Support Motion Detection
- Plastic Casing (front cover metal)

Specification

Model NO. MIB-2P-C

Camera SPEC		Network	
Pixels	2.0 Mega Pixel	Ethernet	RJ-45 (10/100M)
Image Sensor	1/2.9"High-resolution CMOS	Protocol	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, IP Search
Effective Pixels	1920*1080	Protocol Optional	ONVIF2.4
TV System	PAL/NTSC	P2P	Support
Main Stream	1920*1080/1280*720	POE	Support, PoE: (802.3af, Class 3, 36 V to 57 V), 0.25 A to 0.15 A, max. 7.5 W
Sub-stream	704*576/640*360/320*240	Video Delay	0.3S (Within the Lan)
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec	Smart Phone	iPhone, iPad, Android, Android Pad
Usable Illumination	0.001Lux	Frames Per Second	25Fps
S/N Ratio	≥52dB		
Video Output	Network		
Camera Features		Night Vision	
Day/Night	24h Full Color warm light	Supplement Light	2PCS SMT LED (Warm Light)
Compression	H.264/H.265	Light Range	25M
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR, White Balance, BLC, FLK(Flicker Control)	IR Status	Under 10 Lux By CDS
Motion Detection	Support	IR Power On	CDS Auto Control
Privacy Masking	3 Rectangular Zone		
DWDR / WDR	DWDR	General	
Recording Mode	NVR/NAS/CMS/Web	Housing	Plastic (front cover metal)
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian	Bracket	NO
		IR Cut Filter	YES
		Operation Temperature	-10°C ~ +50°C RH95% Max
		Storage Temperature	-20°C ~ +60°C RH95% Max
		Power Source	DC12V±10%, 500mA
		Dimension	188(W) x 60(H) x 65(D)mm
		Weight	Weight: 0.4kg
Lens			
Focus Length	2.8mm F1.3		
Focus Control	Fixed		
Lens Type	Fixed		