



INFINITY MIB-5P-CN

Key Feature

- 5MP Resolution
- 24/7 Full Color
- 2.8mm fixed lens
- H.265 compression
- Light Range up to 25M
- Support ONVIF 2.4
- Support PoE
- Support Motion Detection
- Plastic Casing (front cover metal)

Specification

Model NO. MIB-5P-CN

| Camera SPEC | | Network | |
|-------------------------|--|-----------------------|---|
| Pixels | 5.0 Mega Pixel | Ethernet | RJ-45 (10/100M) |
| Image Sensor | 1/2.5"High-resolution CMOS | Protocol | HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS,IP Filter, PPPOE, DDNS, IP Search |
| Effective Pixels | 2880*1624 | Protocol Optional | ONVIF2.4 |
| TV System | PAL/NTSC | P2P | Support |
| Main Stream | 5MP(2880x1624)/4MP(2500*1660)/3MP(2304*1296)/2MP(1920*1080)/1MP(1280*720) | POE | Support, PoE: (802.3af, Class 3, 36 V to 57 V), 0.25 A to 0.15 A, max. 7.5 W |
| Sub-stream | 448P(800*448)/D1(704*576)/360P(640*360) / CIF(352*288) | Video Delay | 0.3S (Within the Lan) |
| Electronic Shutter Time | Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec | Smart Phone | iPhone, iPad, Android, Android Pad |
| Usable Illumination | 0.001Lux | Frames Per Second | 20Fps |
| S/N Ratio | ≥52dB | | |
| Video Output | Network | | |
| Camera Features | | Night Vision | |
| Day/Night | 24h Full Color warm light | Supplement Light | 2PCS SMT LED (Warm Light) |
| Compression | H.264/H.265 | Light Range | 25M |
| Image Config | Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR, White Balance, BLC, FLK(Flicker Control) | IR Status | Under 10 Lux By CDS |
| Motion Detection | Support | IR Power On | CDS Auto Control |
| Privacy Masking | 3 Rectangular Zone | General | |
| DWDR / WDR | DWDR | Housing | Plastic (front cover metal) |
| Recording Mode | NVR/NAS/CMS/Web | Bracket | NO |
| Language | Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian | IR Cut Filter | YES |
| Lens | | Operation Temperature | -10°C ~ +50°C RH95% Max |
| Focus Length | 2.8mm F1.3 | Storage Temperature | -20°C ~ +60°C RH95% Max |
| Focus Control | Fixed | Power Source | DC12V±10%, 500mA |
| Lens Type | Fixed | Dimension | 188(W) x 60(H) x 65(D)mm |
| | | Weight | Weight: 0.4kg |