



## INFINITY MID-2P-C

### Key Feature

- 2MP Resolution
- 24/7 Full Color
- 2.8mm fixed lens
- H.265 compression
- Light Range up to 25M
- Support ONVIF 2.4
- Support PoE
- Support Motion Detection
- Plastic Casing

### Specification

#### Model NO. MID-2P-C

Camera SPEC	
Pixels	2.0 Mega Pixel
Image Sensor	1/2.9" High-resolution CMOS
Effective Pixels	1920*1080
TV System	PAL/NTSC
Main Stream	1920*1080/1280*720
Sub-stream	704*576/640*360/320*240
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Usable Illumination	0.001Lux
S/N Ratio	≥52dB
Video Output	Network
Camera Features	
Day/Night	24h Full Color warm light
Compression	H.264/H.265
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR, White Balance, BLC, FLK(Flicker Control)
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
DWDR / WDR	DWDR
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
Lens	
Focus Length	2.8mm F1.3
Focus Control	Fixed
Lens Type	Fixed

Network	
Ethernet	RJ-45 (10/100M)
Protocol	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, IP Search
Protocol Optional	ONVIF2.4
P2P	Support
POE	Support, PoE: (802.3af, Class 3, 36 V to 57 V), 0.25 A to 0.15 A, max. 7.5 W
Video Delay	0.3S (Within the Lan)
Smart Phone	iPhone, iPad, Android, Android Pad
Frames Per Second	25Fps
Night Vision	
Supplement Light	2PCS SMT LED (Warm Light)
Light Range	25M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
General	
Housing	Plastic
Bracket	NO
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	105(W) x 95(H) mm
Weight	Weight: 0.3kg