



Key Feature

- Full port supports 6KV lightning protection
- Supports power supply over-temperature, over-voltage and Inrush current protection
- Provides 2 x 10/100M RJ45 uplink ports at the same time
- Supports IEEE 802.3x full-duplex and half-duplex backpressure flow control
- Supports uplink port auto-rollover (Auto MDI/MDIX)
- AI smart buttons
- Complies with IEEE802.3af/at standards, with a maximum PoE power of 30W per port
- Support PoE short circuit, overcurrent, over temperature protection
- Support AI PoE, restart dead devices
- Ease of use (Plug and play / Zero configuration feature)

Spesification

Network interface	<ul style="list-style-type: none"> • 4 x 10/100Mbps PoE-enabled RJ45 ports (ports 1 to 4) • 2 x 10/100Mbps non-PoE function RJ45 ports (ports 5 ~ 6)
Network protocol standards	<ul style="list-style-type: none"> • IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at
Performance specifications	<ul style="list-style-type: none"> • Backplane bandwidth: 1.2Gbps (non-blocking) • Packet forwarding rate: 0.89Mpps • MAC address table: 2K • Forwarding mode: Store-and-forward
LED indicator	<ul style="list-style-type: none"> • Power LED • LINK/ACT indicator • PoE indicator • RESV: Reserved
PoE bits	<ul style="list-style-type: none"> • 1/2(+), 3/6(-)

Power support	<ul style="list-style-type: none"> • Single port maximum output power: 30W • The maximum power supply of the whole machine: 60W
Dimension	<ul style="list-style-type: none"> • Size (length x width x height): 125mm*75mm*27mm
Environmental specifications	<ul style="list-style-type: none"> • Working temperature: 0 °C ~ 40 °C • Storage temperature: -40 °C ~ 70 °C • Working humidity: 10% ~ 90% RH does not condense • Storage humidity: 5%~90% RH non-condensing
Safety specifications	<ul style="list-style-type: none"> • CE/ROHS/FCC/CCC