



Key Feature

- Full port supports 6KV lightning protection
- Supports power supply over-temperature, over-voltage and Inrush current protection
- Provides 2 gigabit RJ45 uplink ports
- Supports IEEE 802.3x full-duplex and half-duplex backpressure flow control
- Supports Auto-flipping of uplink ports (Auto MDI/MDIX)
- AI smart buttons
- Complies with IEEE802.3af/at standards, with a maximum PoE power of 30W per port
- Support PoE short circuit, overcurrent, over temperature protection
- Support AI PoE, restart dead devices
- Ease of use (Plug and play / Zero configuration feature)

Spesification

Network Interface	<ul style="list-style-type: none"> • 8 10/100Mbps RJ45 ports with PoE supported(Port 1~Port 8) • 2 10/100/1000Mbps non-PoE RJ45 ports (Port 9~Port 10)
protocol standard	<ul style="list-style-type: none"> • IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at
Performance Specifications	<ul style="list-style-type: none"> • Backplane bandwidth : 5.6Gbps (non-blocking) • Packet forwarding rate : 4.17Mpps • MAC address table : 2K • Forwarding mode: store and forward
LED indicator	<ul style="list-style-type: none"> • Power Indicator • LINK/ACT Indicator • PoE Indicator • RESV : reserved
PoE pin	<ul style="list-style-type: none"> • 1/2(+), 3/6(-)

Power support	<ul style="list-style-type: none"> • Single port maximum output power: 30W • The maximum power of the whole machine: 96W
Physical Specifications	<ul style="list-style-type: none"> • Dimensions (LxWxH) : 184mm*94mm*27mm
Environmental Specifications	<ul style="list-style-type: none"> • Working temperature: 0°C~40°C • Storage temperature: -40°C ~ 70°C • Working humidity: 10%~ 90% RH without condensation • Storage humidity: 5%~90% RH without condensation
safety regulations	<ul style="list-style-type: none"> • CE/ROHS/FCC/CCC